





GO! Bright Sampler Quilt

finished size 44" x 58" finished block size 12" x 12"



GO!® DIES USED:

- GO! Half Square-2" Finished Triangle (55018 or 55063)
- GO! Square-2½" (55018 or 55059)
- GO! Square-3½" (Quilt Block B 55006)
- GO! Square-4½" (55018 or 55060)
- GO! Half Square-3" Finished Triangle (Quilt Block E 55009)
- GO! Half Square-4" Finished Triangle (55031)
- GO! Triangle-4%" (Quilt Block D 55002)
- GO! Triangle-6½" (Quilt Block C 55001)
- GO! Parallelogram-3¾" x 3½" (Quilt Block G 55004)
- GO! Strip Cutter-2½" (55014 or 55017)

FABRIC REQUIREMENTS

- Fabric $1-1\frac{1}{2}$ yards (includes cornerstones)
- Fabric 2—¾ yard
- Fabric 3—¾ yard
- Fabric 4—¾ yard
- Fabric 5—1⅓ yards (includes binding)
- Fabric 6—% yard
- Backing—2¾ yards (2, 49" widths to be pieced together)
- Batting-48" x 62"

1	2	3	4	5
1	4	4		
	2		6	3
8	2	2	6	4
23	10	20	4	5
	6		4	1
29	5	2	4	
	2	6	1	5
80	27	25	24	20
4		4		
3*				5**
	8 23 29 80 4	1 4 2 8 2 23 10 6 29 5 2 80 27 4	1 4 4 4 2 8 2 2 2 3 10 20 6 29 5 2 6 80 27 25 4 4	1 4 4 2 6 8 2 2 6 23 10 20 4 6 4 29 5 2 4 2 6 1 80 27 25 24 4 4 4



Fabric 6:

• Cut 2—121/2" x width of fabric (WOF) rectangles for sashing. See Cutting Directions with Finishing Directions at end of pattern.

(Also see Cutting Directions for each block and for orientation of G parallelograms.)


- * 2 for cornerstones
- all for binding







BLOCK 1:




CUTTING DIRECTIONS

- Cut 4—Fabric #1, 3" finished half square triangles (Quilt Block E)
- Cut 4—Fabric #2, parallelograms (Quilt Block G)
- Cut 12—Fabric #3, 3" finished half square triangles (Quilt Block E)
- Cut 4—Fabric #4, parallelograms (Quilt Block G)

SEWING DIRECTIONS

- 1. Lay out shapes for block.
- 2. Pin and sew one Fabric #1, E triangle and one Fabric #3, E triangle to sides of Fabric #2, G parallelogram. Press toward G. Make four.






- 5. Pin and sew two quarter blocks together to form half blocks. Press seam open.
- 6. Pin and sew two half blocks together to complete block. Press seam open.







BLOCK 2:



CUTTING DIRECTIONS

- Cut 8—Fabric #1, 3" finished half square triangles (Quilt Block E)
- Cut 4—Fabric #2, 3½" squares (Quilt Block B)
- Cut 2—Fabric #3, 3" finished half square triangles (Quilt Block E)
- Cut 2—Fabric #4, 3" finished half square triangles (Quilt Block E)
- Cut 4—Fabric #5, 4%" triangles (Quilt Block D)
- Cut 4—Fabric #5, 3" finished half square triangles (Quilt Block E)

SEWING DIRECTIONS

- 1. Lay out shapes for block.
- 2. Pin and sew one Fabric #5, and one Fabric #4, E triangle together to form a half square triangle (HST). Make two. Press toward darker fabric.



3. Pin and sew one Fabric #5, and one Fabric #3. E triangle together to form a HST. Make two. Press toward darker fabric.



- 4. Pin and sew HST together to form block center. Press seam open.
- 5. Pin and sew one Fabric #1, E triangle to each side of Fabric #5, D triangle to form flying geese unit. Make four. Press toward D triangle.




- 6. Pin and sew one flying geese unit to top and bottom of block center. Press toward flying geese unit.
- Pin and sew one Fabric #2, B square to each end of two remaining flying geese units. Press toward flying geese unit.
- 8. Pin and sew unit from step 6 to sides of block center to complete block. Press toward added units.







BLOCK 3:



CUTTING DIRECTIONS

- Cut 2—Fabric #1, 4%" triangles (Quilt Block D)
- Cut 1—Fabric #1, 3½" square (Quilt Block B)
- Cut 3—Fabric #1, 3" finished half square triangles (Quilt Block E)
- Cut 1 pair—Fabric #2, parallelogram (Quilt Block G)
- Cut 2—Fabric #3, 4%" triangles (Quilt Block D)
- Cut 3—Fabric #5, 6½" triangles, (Quilt Block C)
- Cut 1—Fabric #5, parallelogram (Quilt Block G)
- Cut 1—Fabric #5, 3" finished half square triangle (Quilt Block E)


SEWING DIRECTIONS

- 1. Lay out shapes for block.
- 2. Pin and sew Fabric #2, G parallelograms together, stopping stitching 1/4" from intersection with Fabric #1, square B as shown by dot on diagram.
- 3. Pin and sew Fabric #1, E triangles to edges of Fabric #2, G shapes. Press seams toward E triangles.
- 4. Pin and sew Fabric #1, B square to Fabric #2, G shapes with a Y seam, starting stitching at 1/4" point for each seam. Press seams toward B square.
- 5. Pin and sew one Fabric #3, D triangle to one Fabric #1, D triangle. Press toward darker fabric. Make two pairs.
- Pin and sew one Fabric #5, C triangle to combined unit from step 5. Press toward triangle C. Make two.
- 7. Pin and sew one Fabric #1, E triangle to side of Fabric #5, G parallelogram. Press toward G parallelogram.
- Pin and sew one Fabric #5, E triangle to top of combined unit from step 7. Press toward G parallelogram.











9. Pin and sew one Fabric #5, C triangle to combined unit from step 8. Press toward triangle C.





11. Pin and sew two block halves together to complete block. Press seam open.

BLOCK 4:




CUTTING DIRECTIONS

- Cut 16—Fabric #1, 2" finished half square triangles
- Cut 4—Fabric #1, 2½" squares
- Cut 1 each—Fabric #2, #3, #4 and #5, 4½" square
- Cut 4 each—Fabric #2, #3, #4 and #5, 2" finished half square triangles

SEWING DIRECTIONS

- 1. Pin and sew one Fabric #1, 2" finished half square triangle (HST) to one Fabric #5, 2" finished HST. Make four. Make four half square triangle units each from Fabric #2, #3 and #4 with Fabric #1 as shown in diagram. Press seams toward darker fabric.
- 2. Lay out block.
- 3. Pin and sew two HST of the same color together as shown. Make one set of each color.
- 4. Pin and sew one combined unit from step 3 to the bottom of the matching color $4\frac{1}{2}$ " square. Press toward 4½" square.
- 5. Pin and sew one Fabric # 1, 2½" square to the bottom of one combined unit from step 3. Press toward white $2\frac{1}{2}$ " square.












BLOCK 4 SEWING DIRECTIONS Cont.

- 6. Pin and sew units together to form quarter of block. Press seams open. Make four.
- Pin and sew two block quarters together to form half blocks. Press seam open. Make two.
- Pin and sew two block halves together to complete block. Press seam open.



BLOCK 5:



CUTTING DIRECTIONS

- Cut 12—Fabric #1, 2" finished half square triangles
- Cut 1—Fabric #2, 4½" square
- Cut 4—Fabric #2, 2½" squares
- Cut 4—Fabric #3, 4½" squares
- Cut 12—Fabric #3, 2" finished half square triangles

SEWING DIRECTIONS

Pin and sew one Fabric #1, 2" finished half square triangle (HST) to one Fabric #3, 2" finished HST. Make 12. Press seams toward darker fabric.




- 2. Lay out corner units.
- 3. Pin and sew two half square triangle units together. Press seam as shown by arrows.
- 4. Combine units to form block corner. Press seam open. Make four.



- 5. Lay out block units.
- 6. Pin and sew units into rows. Press toward Fabric #3, $4\frac{1}{2}$ " squares.
- 7. Pin and sew rows together to complete block. Press seams toward block center.

BLOCK 6:



CUTTING DIRECTIONS

- Cut 8—Fabric #1, 2½" squares
- Cut 24—Fabric #1, 2" finished half square triangles
- Cut 12—Fabric #2, 2" finished half square triangles
- Cut 1—Fabric #3, 4½" square
- Cut 8—Fabric #4, 2" finished half square triangles
- Cut 4—Fabric #5, 2" finished half square triangles

SEWING DIRECTIONS

1. Pin and sew one Fabric #1, 2" finished half square triangle (HST) to one Fabric #5, 2" finished HST. Make four. Press seams toward darker fabric.



- 2. Pin and sew one Fabric #1, 2" finished HST to one Fabric #4, 2" finished HST. Make eight. Press seams toward darker fabric.
- 3. Pin and sew one Fabric #1, 2" finished HST to one Fabric #2, 2" finished HST as shown. Make 12. Press seams toward darker fabric.
- 4. Lay out corner HST.
- Pin and sew HST as shown. Press seams as shown by arrows.



- Combine units to form block corner. Press seam open. Make four.
- 7. Lay out center side units.
- Pin and sew HST and $2\frac{1}{2}$ " squares as shown. Press seams open.




- Combine units to form block center side unit. Press seam open. Make four.
- 10. Lay out block units.
- 11. Pin and sew units together into rows. Press seams open or toward Fabric 33, 4½" square.
- 12. Pin and sew rows together to complete block. Press seams open.







BLOCK 7:



CUTTING DIRECTIONS

- Cut 1—Fabric #1, 2½" strip across the width of fabric (WOF) Sub cut $4-2^{1/2}$ " x $8^{1/2}$ " rectangles
- Cut 8—Fabric #1, 2" finished half square triangles
- Cut 4—Fabric #4, 2½" squares
- Cut 12—Fabric #4, 2" finished half square triangles
- Cut 12—Fabric #5, 2" finished half square triangles


SEWING DIRECTIONS

1. Pin and sew one Fabric #4, 2" finished half square triangle (HST) to one Fabric #5, 2" finished HST. Make eight. Press seams toward darker fabric.



- 2. Pin and sew one Fabric #1, 2" finished HST to one Fabric #5, 2" finished HST. Make four. Press seams toward darker fabric.
- 3. Pin and sew one Fabric #1. 2" finished HST to one Fabric #4, 2" finished HST. Make four. Press seams toward darker fabric.
- 4. Lay out 16 unit block center.
- 5. Pin and sew into rows. Press each row in alternating directions.
- Pin and sew rows together to complete block center. Press
- 7. Pin and sew one Fabric #1, 2½" x 8½" rectangle to sides of block center. Press seams toward rectangles.
- 8. Pin and sew one Fabric #3/#5 HST to each end of two, 2½" x 8½" rectangles. Press seams toward rectangles.
- Pin and sew combined unit to top and bottom of expanded block center to complete block. Press seams toward added units.

BLOCK 8:




CUTTING DIRECTIONS

- Cut 8—Fabric #2, 3" finished half square triangles (Quilt Block E)
- Cut 4—Fabric #3, 3½" square (Quilt Block B)
- Cut 4—Fabric #4, 6½" triangles, (Quilt Block C)

SEWING DIRECTIONS

- 1. Pin and sew two Fabric #2, E triangles to sides of one Fabric #3, B square as shown. Press seams toward added triangles. Make four.
- 2. Pin and sew one Fabric #4, C triangle to combined unit in step 1. Press seam toward C triangle. Make four.
- 3. Lay out block units.
- 4. Pin and sew together into two half blocks. Press seam toward C triangles.
- 5. Sew half blocks together to complete block. Press seam open.

BLOCK 9:



CUTTING DIRECTIONS

- Cut 4—Fabric #1, 4%" triangles (Quilt Block D)
- Cut 8—Fabric #1, 3" finished half square triangles (Quilt Block E)








BLOCK 9 CUTTING DIRECTIONS Cont.

- Cut 8—Fabric #3, 3" finished half square triangles (Quilt Block E)
- Cut 4—Fabric #4, 4%" triangles (Quilt Block D)


SEWING DIRECTIONS

- 1. Lay out two Fabric #3, and two Fabric #1, E triangles as shown.
- Pin and sew together in pairs. Press seams toward darker triangles.



- Pin and sew two combined units together. Press seam open. Make 2.
- 5. Pin and sew 2 combined units from Step 4 together to complete block center.
- 6. Pin and sew one Fabric #4, and one Fabric #1, D triangle together for block corners taking care to not stretch bias edges. Press seam toward Fabric #4 triangles. Make four.
- 7. Lay out block units.
- 8. Pin and sew corners to block center, matching seams, to complete block. Press seams toward corner units.

BLOCK 10:



CUTTING DIRECTIONS

- Cut 2—Fabric #1, 4%" triangles (Quilt Block D)
- Cut 2—Fabric #2, 6½" triangles, (Quilt Block C)
- Cut 4—Fabric #2, 47/8" triangles (Quilt Block D)
- Cut 2—Fabric #4, 6½" triangles, (Quilt Block C)
- Cut 2—Fabric #4, 47/8" triangles (Quilt Block D)


SEWING DIRECTIONS

- 1. Pin and sew one Fabric #4. D triangle to one Fabric #1 triangle. Press seam toward darker fabric. Make two.
- 2. Pin and sew two Fabric #2, D triangles together. Press seam open. Make two.
- Pin and sew combined units from Steps 1 and 2 together. Press seam toward Fabric #2 unit. Make two.
- 4. Pin and sew combined units from Step 3 together to complete block center. Press seam open.
- Pin and sew corner triangles to block center to complete block taking care to not stretch bias edges. Press seams toward corner triangles.

6 of 7



BLOCK 11:



CUTTING DIRECTIONS

- Cut 4—Fabric #1, 4" finished half square triangles
- Cut 2—Fabric #1, 2½" squares
- Cut 4—Fabric #3, 4" finished half square triangles
- Cut 2—Fabric #3, 2½" squares
- Cut 4—Fabric #5, 4½" squares

SEWING DIRECTIONS

- 1. Pin and sew one Fabric #3, 2½" square and one Fabric #1, 2½" square together. Press seam toward green square. Make two.
- 2. Pin and sew combined squares into 4-Patch. Press seam open.
- Pin and sew one Fabric #3, 4" finished half square triangle (HST) to one Fabric #1, 4" finished HST. Press seam toward darker fabric. Make four.
- 4. Lay out block units.








BLOCK 11 SEWING DIRECTIONS Cont.

- 5. Pin and sew together into rows. Press seams toward Fabric #5, $4\frac{1}{2}$ " squares.
- 6. Pin and sew rows together to complete block. Press seams toward block center.

BLOCK 12:



CUTTING DIRECTIONS

- Cut 15—Fabric #1, 2½" squares
- Cut 20—Fabric #1, 2" finished half square triangles
- Cut 11— Fabric #2, 2" finished half square triangles
- Cut 1—Fabric #2, 2½" square
- Cut 9—Fabric #3, 2" finished half square triangles

SEWING DIRECTIONS

1. Pin and sew one Fabric #1, 2" finished half square triangle (HST) to one Fabric #3, 2" finished HST. Make nine. Press seams toward darker fabric.



- Pin and sew one Fabric #1, 2" finished HST to one Fabric #2, 2" finished HST. Make nine. Press seams toward darker fabric.
- 3. Lay out block units.
- 4. Pin and sew into rows. Press each row in alternating directions.
- Pin and sew rows together to complete block. Press toward bottom of block.

QUILT FINISHING DIRECTIONS

Measure completed blocks. Factor an average size square. As seam allowances vary, your blocks may or may not measure $12\frac{1}{2}$ " square. Use your measurement.

CUTTING DIRECTIONS

Fabric 1:

- Cut 2—2½" strips across the WOF for cornerstones Sub cut 20—2½" squares
- Place 2½" strips on Strip Cutter-2½" die perpendicular to blades to cut 20—2½" squares.

Fabric 5:

• Cut 5—2½" strips across the WOF for binding

- Cut 2—12½" (*or use your measurement here) x width of fabric (WOF) rectangles
- Fan fold one rectangle and place on Strip Cutter-2½" so straight grain of fabric is going through roller. Trim fabric rectangle as needed. Cut a total of $3\bar{1}$ — $2\frac{1}{2}$ "* x $12\frac{1}{2}$ " sashing pieces.

Backing fabric:

• Cut 2—49" x WOF rectangles

SEWING DIRECTIONS

- 1. Lay out blocks according to diagram.
- 2. Label blocks 1 12.
- 3. Pin and sew vertical Fabric #6 sashing pieces between blocks as shown. Press seams toward sashing pieces.
- 4. Pin and sew three horizontal sashing pieces and four, 2½" square Fabric #1 cornerstones together. Press seams toward sashing pieces.
- Pin and sew combined sashing units between rows and top and bottom of quilt. Press seams toward sashing.
- 6. Remove any markings.
- 7. Press quilt top.
- 8. Piece backing fabric. Trim off selvages from one edge of each 49" x width of fabric rectangle. Pin and sew together with a 1/4" seam along 49" length. Press seam open.

QUILTING AND FINISHING

- 1. Layer batting between quilt top and backing.
- 2. Pin or baste layers together.
- 3. Quilt as desired. Model was machine quilted with an all-over design.
- 4. Add binding, mitering corners.